Philips
S-video cable

3.0 m

SWV2513

Ensure a reliable connection

with this S-Video cable

Depend on this cable to provide you with a reliable video connection between components.

Enjoy good picture quality
- Nickel-plated connectors for reliable contact

Protects against signal loss
- Bare copper shielding

Easy installation
- Non-slip ergonomic grip for easy use

Enjoy extended durability
- Molded plug for secure connections
- Flexible PVC jacket

PHILIPS
sense and simplicity

S-video cable
3.0 m

SWV2513/93

Specifications

Inner Carton
- EAN/UPC/GTIN: 87 10895 96663 4
- Quantity: 6
- Gross weight: 0.80 kg
- Tare weight: 0.20 kg
- Net weight: 0.60 kg
- Length (cm): 22.9 cm
- Width (cm): 11.4 cm
- Height (cm): 20.8 cm

Outer Carton
- EAN/UPC/GTIN: 87 10895 96664 1
- Quantity: 12
- Gross weight: 1.90 kg
- Tare weight: 0.30 kg
- Net weight: 1.60 kg
- Length (cm): 24.9 cm
- Width (cm): 24.4 cm
- Height (cm): 22.9 cm

Packaging
- EAN/UPC/GTIN: 87 10895 95207 1
- Gross Weight: 0.10 kg
- Tare Weight: 0.02 kg
- Net Weight: 0.08 kg
- Height: 3.0 cm
- Length: 27.9 cm
- Width: 22.5 cm

Product highlights

Nickel-plated connectors
Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

Bare copper shielding
Bare copper shielding protects against signal loss.

Easy grip
This non-slip grip makes connecting your components easy and ergonomically comfortable.

Molded plug
Molded plugs ensure secure connections between components and offer extended durability.

Flexible PVC Jacket
Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Issue date 2007-12-07
Version: 1.0.5
12 NC: 9082 100 07472
EAN: 87 10895 95207 1

© 2007 Koninklijke Philips Electronics N.V.
All Rights reserved.
Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com